

Material Safety Data Sheet

1、Identification of the material and company

Material identity: Trade name : TAISOX 7130F、7140F、7310M、7320M、7240M、7340M、7440M、 7350M(F)、7360M、7470M、7620M、7650M、7660M、7760H、7870H、 7920M、7A50H、7B50H、7A60H、7B60H、7470K
Material NO:TC-1057
Producer/Supplier: Formosa Plastics Corporation Formosa Industrial Park No.1, Mailiao, Yunlin county, Taiwan
Emergency Phone / Fax : 886-5-6811180/886-5-6811122

2、Hazard indication:

3.1 Referring to EEC directive 88/379, the material is classified <u>NOT DANGEROUS</u> .
3.2 Main personal hazards: -fire, see §5 -Slipping in case of spillage/leakage, see §6 -Inhalation of vapors, fumes, powders, see §7 -Hazard of contact with molten polymer, see §4
3.3 Powders have specific fire risks
3.4 Environment: Lack of biodegradability, see§12

3、Composition / Information on Ingredients

Technical name : EVA copolymer
Chemical name : Ethylene vinyl acetate copolymer
Ingredient percent(%): EVA≥99.9%、Other≤0.1%
Chemical Abstracts Number (CAS No.) : 24937-78-8
Symbol of the basic polymer against standard ISO 1043-1 : E/VAC
Dangerous components: NONE

4、First Aid Measures :

Skin: If molten polymer gets on skin, cool rapidly with cool water. Burns have to be treated clinically.
EYES: Wash abundantly with water.

5、Fire Fighting Measure :

Suitable Extinguishing Media: Water, Water fog, CO2, Foam or dry extinguishers
Extinguishing Media to be avoided: NONE
Combustion products: Carbon dioxide, water. In case of incomplete combustion: carbon monoxide, hydrocarbons, aldehydes, ketones and acetic acid may be developed.

6 · Spillage

In case of spillage/leakage scoop to container to avoid danger of skidding.

7 · Handling and Storage

7.1 During the processing of the material, avoid inhalation of fumes, or powders, by providing good ventilation of the workroom and, if necessary, they have to be trapped by intake in an effective manner. If these measures are taken, traces of aldehydes or ketones which may arise during the process, will remain under the TLV/TWA value. Avoid dispersion of dust in air to reduce potential for ignition or explosions.

7.2 Storage: Out of direct sun, in well ventilated, cool and dry places

7.3 fire precautions: Equipment must be earthed, to avoid static electric charges. Any contact with flame or hot surface must be avoided.

8 · Personal Protection

Use gloves, goggles or eyeshade and normal working equipment.

In case of powder, avoid inhalation.

9 · Physical and Chemical Properties / Characteristics

Appearance: Solid	Form : Pellet
Color : Translucent	Odor: Slight ester odor.
pH value : -	Boiling Point / Boiling Range: °C
Decomposition Temperature : -	Flash Point : 500 °F 260 °C Test Method : <input type="checkbox"/> Open Cup <input checked="" type="checkbox"/> Close Cup
Auto ignition Temperature : ca.300°C	Exposure Limits : - %
Vapor Pressure : - (Below) mmHg@20°C	Vapor Density : -
Specific Gravity : 0.920-0.960 g/cm ³	Solubility in Water : negligible
Melting point/ Freezing point: -	Volatility: -
n-octanol partition coefficient (lgKow): -	

10 · Stability and Reactivity

Stable and chemically inert at room temperature. Protracted exposure to temperature over 200°C may cause resin degradation.

11 · Toxicological Information

Exposures limits for vinyl acetate: TLV-TWA 10ppm(35mg/m³),STEL 15 ppm(35mg/m³);TWA for dust:5 mg/m³

Avoid exposure to fumes, eventually developed during the process, by intake and/or efficient ventilation of the working rooms.

12 · Ecological Information

The product is not biodegradable. It can be recycled using suitable technologies. It does not contain, as additives, compounds of lead, mercury, cadmium and chromium. It does not contain asbestos, CFC, HCFC; halides .It is not a water endangering material. It is very slowly degraded by solar UV irradiation.

13 · Disposal Information

Disposal must be done in accordance with existing regulations. Landfilling and incineration can be considered in most cases suitable. Recycling is possible by melting and pelletizing.

14 · Transport Information

14.1 According to RIR-ADR, IMO, IATA, IMDG, FS A11 the product is not dangerous.

14.2 On loading and unloading, equipment must be earthed to avoid static electric charges.

15 · Regulation Information

None

16 · Other Information

The information provided is given in good faith and is based on our actual knowledge.
This is not a technical sheet for use of the product.
This sheet does not exempt the user from knowing and applying all the relevant regulations and from taking all the relevant safety precautions.

Producer	Polyolefin Div., Formosa Plastics Corp.
Prepared by	Wei-Yun Chang (Engineer)
Revision 2015-03-12	